

**TECHNICAL****DATA****BULLETIN NO. 315**

TURCO PRODUCTS • A DIVISION OF PUREX CORPORATION, LTD. • WILMINGTON, CALIFORNIA 90744 • OFFICES IN ALL PRINCIPAL CITIES

Date: April 14, 1967
 Revision Date: March 1970

TURCO[®] 5351

NEUTRAL EPOXY, POLYURETHANE PAINT STRIPPER

DESCRIPTION

TURCO 5351 is a thickened, essentially neutral, no acid or free alkali, paint stripper which effectively strips paint, including epoxy, polyurethane and similar organic coatings from metal surfaces.

PROPERTIES

Appearance: Heavy Bodied, yellow liquid.

Cling: Excellent on all surfaces, vertical or horizontal.

Evaporation: Self-forming surface film which retards evaporation and extends working life.

Corrosion Data: 7 days at 100°F. (mg. weight change - 1 x 2 inch panels)

Mg.	=	0.0
Dow 7	=	0.0
1100 Al	=	-0.1
2024 Al	=	0.0
1020 Steel	=	0.0
Cad. Plated Steel	=	-0.1
Tin	=	-0.1

Safe on high strength steel per the following test procedures:
 Passes notched "C" ring embrittlement test of specification TT-R-248.
 Douglas Stressed Ring
 Lawrence Hydrogen Detection Gauge

USE INSTRUCTIONS

Equipment: TURCO Barrel Pump. TURCO Sprayer, or similar nonatomizing spray equipment. May also be applied by brush.

Concentration: Apply TURCO 5351 full strength, as received.

Stripping: Allow TURCO 5351 sufficient dwell time for thorough loosening of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush.

Rinsing: TURCO 5351 and paint residues may be rinsed with high pressure, high volume cold water, or with a steam cleaning machine. Slight brushing during the rinse operation insures complete removal of all residues.

LIMITATIONS

CAUTION: TURCO 5351 contains chlorinated solvents and phenolic bodies. Avoid contact with skin, eyes and clothing. Use with adequate ventilation. Face shields or goggles, and protective solvent-resistant gloves and clothing are recommended for using personnel. Refer to product label for additional precautionary and handling information.

TURCO 5351 will attack plastics, therefore Plexiglas windows should be protected. Also protect rubber window seals and tires.

PACKAGING

TURCO 5351 is packaged in 5 and 55 gallon containers.

SHIPPING

The product is packed in approved I.C.C. containers and can be sent via truck, rail, ship, railroad express, parcel post (if in a suitable container) anywhere within the Continental limits of the United States.

NOTICE

The information and recommendations of TURCO concerning this product are based upon our laboratory tests and field use experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied.

Turco certifies that his product as furnished to the customer is of the same formulae and quality as the samples submitted for approval test.